



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

Specification Sheet For Model GE 2400 P / GE 2400 PS



		Model Name	GE - 2400 P / PS
Generator	Special Highlight		<ul style="list-style-type: none"> 2.1 KVA Genset With Simple Design & Having Low Maintenance & Long Life.
	Application		<ul style="list-style-type: none"> General Purpose Use For Homes, Shops Photo Copier, Computer Laptops, Printers, Commercial Use Or Field Jobs For Running Electrical Loads of 2.1 KVA Capacity.
	*Max AC. Output VA		2100
	*Rated AC. Output VA		1800
	Rated Current Amps		7.8
	NFB Amps		8
	AC. Voltage at Rated Load		225 Volts \pm 10 Volt 50 Hz, Single Phase
AC. Voltage at No Load		225 Volts \pm 10 Volt	
Alternator	#Alternator Max. Current Capacity		10 Amps.
	Alternator		Self-Excitation & Constant Voltage (With AVR), THD \leq 25%,
Engine	Model		HM170P
	Type		OHV25°Inclined,Single Cylinder,4 Strokes, S.I, Forced Air Cooling
	Maximum Power		6.5 HP @ 3600
	Bore x Stroke		70x58 mm



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

	Displacement	223cc
	Starting System	Recoil Start + Self Start
	Fuel	Petrol + LPG (Optional)
	Fuel Tank Capacity	Petrol -12 Ltr.
	Fuel Consumption	Petrol 1.1 ltr/hr, LPG: 650gm./hr.
	Continues Running (With One Filling)	11 Hrs.
	Lube. Oil Capacity	600 ml.
	Lubricating Oil Consumption	2.5 gm./Hr.
	Sound level (Db) (from 1 meter)	<86Db
Panel & Other Standard Features	Voltmeter	Yes (Analogue)
	Digital Hour Meter	No
	Oil Alert System	Yes
	LPG/ Gas Fuel Compatibility	Yes (Optional)
	AMF Panel Auto & Remote Start Compatibility	No
	Fuel Level Gauge	Yes
	Overload Protection (NFB)	Yes
	Costar Wheels	Optional
	Gross weight-KG (with Battery)	39.5 Kg / 44.5 KG
Size & Weight	Dimension LxWxH (mm)	600 x 450 x 530
	Battery Specification	12 Volt 9 Ah Size =135×75×140 (L×W×H)
Specifications are for reference only, Because of continuous improvements and up-gradation by our R&D team. This specifications can change without any prior intimation		