



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

Specification Sheet For Model GE 7000 PS



	Model Name	GE 7000 PS
Generator	Special Highlights	<ul style="list-style-type: none"> • Low Priced & Economical Generator. • Powerful 5.5 KVA Portable Generators, Runs 1.5 Ton Air Conditioner + Other Loads.
	Application	<ul style="list-style-type: none"> • General Purpose Portable Generator, suitable for household, offices, Nursing Homes & Restaurants, Banks & ATMs, Field Jobs etc.
	*Max AC. Output VA	5500
	*Rated AC. Output VA	5000
	Rated Current Amps	21.8
	NFB Amps	22
	AC. Voltage at Rated Load	225 Volts \pm 10 Volt 50 Hz, Single Phase
	AC. Voltage at No Load	225 Volts \pm 10 Volt
Alternator	#Alternator Max. Current Capacity	24 Amps.
	Alternator	Self-Excitation & Constant Voltage (With AVR), THD \leq 25 %,
Engine	Model	HM192PY
	Type	OHV25°Inclined,Single Cylinder,4 strokes, S.I, Forced Air Cooling
	Maximum Power	16.0 hp @ 3600rpm



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

	Bore x Stroke	92×67 mm
	Displacement	445 cc
	Starting System	Recoil Start and Self Start + Remote Start
	Fuel	Petrol
	Fuel Tank Capacity	20.5 Ltr.
	Fuel Consumption	Petrol 2.8 ltr/hr
	Continues Running (With One Filling)	7.5 Hrs.
	Lube. Oil Capacity	1200 ml.
	Lubricating Oil Consumption	4.3 gm./Hr.
	Sound level (Db) (from 1 meter)	<86 Db
Panel & Other Standard Features	Voltmeter	Yes (Digital)
	Digital Hour Meter	Yes
	Oil Alert System	Yes
	LPG/ Gas Fuel Compatibility	Yes (Optional)
	AMF Panel Auto & Remote Start Compatibility	Yes
	Fuel Level Gauge	Yes
	Overload Protection (NFB)	Yes
	Costar Wheels & Handle Sets	Yes
	Gross weight-KG (With Battery)	86 KG
Size & Weight	Dimension LxWxH (mm)	670 x 510 x 670 mm
	Battery Specification	12 Volt 25 Ah Size =190×120×225 (L×W×H)

Specifications are for reference only, Because of continuous improvements and up-gradation by our R&D team. This specifications can change without any prior intimation