



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

Specification Sheet For Model GE 7000 PS



	Model	SILENT GE 7000 PS
Generator	Special Highlights	<ul style="list-style-type: none"> • Very Low Noise, Super Silent Portable Petrol Generator. Option to Run On LPG Fuel Available. • Powerful 5.5 KVA Portable Generators, Runs 1.5 Ton Air Conditioner + Other Loads.
	Application	<ul style="list-style-type: none"> • For Running 1.5 Ton Air Condition, Office Use, Home Use, Small Institution, Computer Center, Nursing Home School Cyber Café Small Banks ATM etc.
	Max AC. Output VA	5500
	Rated AC. Output VA	5000
	Rated Current Amps	21.8
	NFB Amps	22
	AC. Voltage at Rated Load	225 Volts ± 10 Volt 50 Hz, Single Phase
	AC. Voltage at No Load	225 Volts ± 10 Volt
	Alternator	#Alternator Max. Current Capacity
Alternator		Self-Excitation & Constant Voltage (With AVR), THD ≤ 25 %,
Engine	Model	HM192PY
	Type	OHV25°Inclined,Single Cylinder,4 strokes, S.I, Forced Air Cooling
	Maximum Power	16.0 hp @ 3600rpm
	Bore x Stroke	92×67 mm



HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

	Displacement	445 cc
	Starting System	Recoil Start + Self Start
	Fuel	Petrol
	Fuel Tank Capacity	20 Ltr.
	Fuel Consumption	Petrol 2.8 ltr/hr
	Continues Running (With One Filling)	7.5 Hrs.
	Lube. Oil Capacity	1200 ml.
	Lubricating Oil Consumption	4.3 gm./Hr.
	Sound level (Db)	<72Db
Panel & Other Standard Features	Voltmeter	Digital
	Digital Hour Meter	Yes
	Oil Alert System	Yes
	LPG/ Gas Fuel Compatibility	Yes
	Remote Start / AMF Panel	Optional
	Fuel Level Gauge	Yes
	Overload Protection (NFB)	Yes
	Costar Wheels	Yes
	Gross weight-KG (with Battery)	136 Kg
Size & Weight	Dimension LxWxH (mm)	990x530x710 mm
	Battery Specification	12 Volt 25 Ah Size =190×120×225 (L×W×H)

Specifications are for reference only, Because of continuous improvements and up-gradation by our R&D team. This specifications can change without any prior intimation