



# HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,  
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: hpmgenset@gmail.com

## Specification Sheet For Model GE 9000 RS



	Model	SILENT GE 9000RS
Generator	Special Highlights	<ul style="list-style-type: none"> <li>World's Most Powerful &amp; Most Light Weight 8.5 KVA Portable Gasoline Generator.</li> <li>Very Low Noise, Super Silent Portable Petrol Generator. Option to run on LPG Fuel available</li> <li>Pure sine wave THD&lt;5%, also Suitable for sensitive electronic equipment's.</li> <li>Very high over loading capacity, Useful for heavy Industrial Loads.</li> </ul>
	Application	<ul style="list-style-type: none"> <li>Low Priced &amp; Economical Generator</li> <li>Most Suitable for Construction Machinery, running Air Conditioners, Submersible Pump, Deep Freezers, Inductive &amp; Industrial Loads.</li> <li>Very suitable for Field Jobs, Constructions sites, Ambulance, Fire Fighting vehicles, OBM Vans, Industrial Applications, Plasma cutting machine 6.5 KVA, Farm Houses.</li> <li>Runs , 2 units of 1.5 Ton Air Conditioners + other load comfortably.</li> </ul>
	Max AC. Output VA	8500
	Rated AC. Output VA	7000
	Rated Current (Amps)	30.5
	NFB Amps	31
	AC. Voltage at Rated Load	220 Volts $\pm$ 10 Volt 50 Hz, Single Phase
	AC. Voltage at No Load	250 Volts $\pm$ 5 Volt



# HIMALAYAN POWER MACHINE MFG. CO.

Part of Khasra No. 51 and 52 Ka, Village Kuanwala, Haridwar Road, Dehradun,  
Uttarakhand – 248001

Phone No.: +91-9412052496

Email: [hpmgenset@gmail.com](mailto:hpmgenset@gmail.com)

Alternator	#Alternator Max. Current Capacity	48 Amps.
	Alternator	Brushless, Rare Earth Magnetic Rotor, THD 5 %,Pure Sine Wave
Engine	Model	HM192PY
	Type	OHV25°Inclined,Single Cylinder,4 strokes, S.I, Forced Air Cooling
	Maximum Power	16.0 hp @ 3600rpm
	Bore x Stroke	92×67 mm
	Displacement	445 cc
	Starting System	Recoil Start and Self Start + Remote Start
	Fuel	Petrol
	Fuel Tank Capacity	20 Ltr.
	Fuel Consumption	Petrol 3.2 ltr/hr
	Continues Running (With One Filling)	6.5 Hrs.
	Lube. Oil Capacity	1200 ml.
	Lubricating Oil Consumption	4.3 gm./Hr.
	Sound level (Db)	<72Db
Panel & Other Standard Features	Voltmeter	Digital
	Digital Hour Meter	Yes
	Oil Alert System	Yes
	LPG/ Gas Fuel Compatibility	Yes (Optional)
	Remote Start / AMF Pannel	Yes (Optional)
	Fuel Level Gauge	Yes
	Overload Protection (NFB)	Yes
	Costar Wheels	Yes
	Gross weight-KG (with Battery)	146 KG
Size & Weight	Dimension LxWxH (mm)	990x530x710 mm
	Battery Specification	12 Volt 25 Ah Size =190×120×225 (L×W×H)

Specifications are for reference only, Because of continuous improvements and up-gradation by our R&D team. This specifications can change without any prior intimation